

ALGE D-LINE LED DISPLAYS



A cost-effective, lightweight solution to your display needs.
Available in both Indoor and Outdoor models.

OVERVIEW

These new LED displays are both extremely lightweight and extremely affordable. They are fully compatible with all existing Alge timers as well as standard RS-232 interfaces. Available in numerous sizes and configurations, for both indoor and outdoor use.

ALGE D-LINE DESCRIPTION

- ? Direct control by any Alge timer or RS-232 serial device (using banana plugs)
- ? Only about 2 1/2" deep, and super-lightweight!
- ? Powered by either AC power (100-240VAC) or external 12VDC car battery; unlike Alge GAZ displays this unit does NOT contain an internal battery!
- ? Available with optional PST supplementary housing with onboard battery
- ? Internal clock allows unit to function as stand-alone time of day clock, temperature indicator, or stopwatch, using external button
- ? Separate models available for indoor and outdoor use: indoor models use less-intense LEDs than the outdoor models
- ? Several available add-on accessories such as GPS, DCF & data receivers for time of day synchronization and wireless data reception
- ? All standard models feature 6 numeric 7-segment digits
- ? Connections include banana jacks for data input (RS232C), banana jacks for external button, 4-pin Amphenol connector for data or power input
- ? Built-in power supply: 100-240VAC, 50-60hz
- ? Features (2) eyelets on top rear for hanging, plus a standard 3/8" tripod socket on the bottom
- ? Anodized aluminum case with plexiglass face
- ? Operating range: -20C to +60C

ACCESSORIES & ADD-ONS

The D-Line Display is designed to work with the following accessories:

- DCF-radio receiver (Western Europe)
- GPS-radio receiver (Worldwide)
- Temperature sensor (max. 2 sensors)
- Humidity sensor
- Ethernet Socket (for time synchronization)
- RS 485 interface

D-LINE MODELS AVAILABLE

Several standard models are available, and custom configurations are available upon request. Standard INDOOR models include character heights of 2", 4", 6", 12", 18", and 24". Standard OUTDOOR models are available in character heights of 6", 12", 18", and 24".

COMPATIBILITY STATEMENT

This product family is fully compatible with all existing **Alge & PST** products.